



TYPE APPROVAL CERTIFICATE

Certificate No:
TAE00002J5
Revision No:
2

This is to certify:

That the Category cables

with type designation(s)

InduData Cat 5e S/FTP 4 x 2 x 0,22mm² AWG 24/7 stranded,
InduData Cat. 6A S/FTP 4 x 2 x 0,246mm² (7 x 0,212mm) stranded 66J212-008,
InduData Cat. 6A S/FTP 4 x 2 x 0,246mm² (1x0,56mm) solid 66J56-008,
InduData Cat 7 S/FTP 4 x 2 x 0,27mm² AWG 22/7 stranded,
InduData Cat 7 S/FTP 4 x 2 x 0,259mm² AWG 23/1 solid,
InduData Cat. 7A S/FTP 4 x 2 x 0,264mm² (1x0,58mm) solid 72J58-008

Issued to

B.V. Twentsche Kabelfabriek
Haaksbergen, Netherlands

is found to comply with

DNV rules for classification – Ships, offshore units, and high speed and light craft

Application :

Data communication cable, installation/horizontal cable

Products approved by this certificate are accepted for installation on all vessels classed by DNV.

Issued at **Høvik** on **2023-04-17**

for **DNV**

This Certificate is valid until **2027-12-30**.

DNV local unit: **Jiangyin**

Approval Engineer: **Ivar Bull**

.....
Frederik Tore Elter
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 251

Revision: 2022-12

www.dnv.com

Page 1 of 4

Product description

Construction:

Construction	
Conductor	Stranded or solid plain or tinned copper
Insulation	Foam PE
Twisting/ screens	Individual laminated aluminium tape + overall tinned copper braid
Outer sheath	SHF1

Transmission properties:

Cat. 5e S/FTP 4 pair cable

Transmission Frequency(MHz)	1	4	8	10	16	20	25	31,25	62,5	100
Attenuation dB/100m	2,1	4,1	5,8	6,5	8,3	9,3	10,4	11,7	17,0	22,0
Return Loss dB/100m	20,0	23,0	24,5	25,0	25,0	25,0	24,3	23,6	21,5	20,1
PSNEXT dB/100m	62,3	53,3	48,8	47,3	44,2	42,8	41,3	39,9	35,4	32,3

Cat. 6A S/FTP 4 pair cable – 66J212-008 and Cat. 6A S/FTP 4 pair cable – 66J56-008:

Transmission Frequency(MHz)	1	4	10	16	20	31,25	62,5	100	200	250	400	500
Attenuation dB/100m	2,1	3,8	5,9	7,5	8,4	10,5	15,0	19,1	27,6	31,1	40,1	45,3
Return Loss dB/100m	20	23	25	25	25	23,6	21,5	20,1	18,0	17,3	17,3	17,3
PSNEXT dB/100m	72,3	63,3	57,3	54,2	52,8	49,9	45,4	42,3	37,8	36,3	33,3	31,8

Cat. 7 S/FTP 4 pair cable – 70J212-008 and Cat. 7 S/FTP 4 pair cable – 70J56-008::

Transmission Frequency (MHz)	1	4	10	16	20	30	31,25	62,5
Attenuation dB/100m	2,0	3,7	5,9	7,4	8,3	10,2	10,4	14,9
Return Loss dB/100m	20	23	25	25	25	23,8	23,6	21,5
PSNEXT dB/100m	75	75	75	75	75	75	75	72,5

Transmission Frequency (MHz)	100	155	200	250	300	600
Attenuation dB/100m	19,0	24,0	27,47	31,0	34,2	50,1
Return Loss dB/100m	20,1	18,8	18,0	17,3	17,3	17,3
PSNEXT dB/100m	69,4	66,5	64,9	63,4	62,2	57,7

Cat. 7A S/FTP 4 pair cable – 72J58-008:

Transmission Frequency (MHz)	1	4	10	16	20	25	31,25	62,5
Attenuation dB/100m	2,1	3,7	5,8	7,3	8,2	9,2	10,3	14,6
Return Loss dB/100m	20	23	25	25	25	24,3	23,6	21,5
PSNEXT dB/100m	75	75	75	75	75	75	75	75

Transmission Frequency (MHz)	100	200	250	300	500	600	800	1000
Attenuation dB/100m	18,5	26,5	29,7	32,7	42,8	47,1	54,9	61,9
Return Loss dB/100m	20,1	18,0	17,3	17,3	17,3	17,3	16,1	15,1
PSNEXT dB/100m	72,4	67,9	66,4	65,2	61,9	60,7	58,9	57,4

Manufactured by

Zhangjiagang Twentsche Cable Co., Ltd.,
 Jiangsu, China

Application/Limitation

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

In order to achieve a transmission link compliant with Category 7, cables shall be installed with suitable termination equipment according to manufacturer's recommendations.

Type Approval documentation

Datasheets:

56J20-008, ver. 2012-ZTC-12-06

70J223-008, ver. 2012-ZTC-12-06

70J56-008, ver. 2012-ZTC-12-06

TKF data sheet 24031 Cat.6A S/FTP Marine Approved 4 x 2 x AWG 23/1 dated 5/23/2019

TKF data sheet 24032 Cat.6A S/FTP Marine Approved 4 x 2 x AWG 23/7 dated 5/23/2019

TKF data sheet 24023 Cat.7A S/FTP Marine Approved 4 x 2 x AWG 23/1 dated 5/23/2019

Test reports :

China National Center for Quality Supervision and Test of Electric Wire and Cable; report CT12-5505-1

China National Center for Quality Supervision and Test of Electric Wire and Cable; report CT12-5505-2

China National Center for Quality Supervision and Test of Electric Wire and Cable; report CT12-5505-3

Tests carried out

Standard	Release	General description	Limitation
IEC 61156-5	2020-04	Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Horizontal floor wiring - Sectional specification	Reference to requirement for category cable: 5e (100MHz), 7 (600MHz),
IEC 60092-360	2021-01	Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables	

Standard	Release	General description	Limitation
IEC 60332-3-22	2018-07	Tests on electric and optical fibre cables under fire conditions - Part 3-22: Test for vertical flame spread of vertically mounted bunched wires or cables - Category A	Charred portion of sample does not exceed 2,5m above bottom edge of burner.
IEC 60332-3-24	2018-07	Tests on electric and optical fibre cables under fire conditions - Part 3-24: Test for vertical flame spread of vertically mounted bunched wires or cables - Category C	Charred portion of sample does not exceed 2,5m above bottom edge of burner.
IEC 60332-1-2	2004-07	Tests on electric and optical fibre cables under fire conditions – Part 1-1: Test for vertical flame propagation for a single insulated wire or cable – Apparatus	Flame retardant small scale
IEC 60754-2	2019-11	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity	Halogen free: pH > 4,3 Conductivity < 10µS/mm
IEC 61034-1/2	2019-11	Measurement of smoke density of cables	IEC 61034-1/2

Marking of product

TKF - InduData - Category 5E S/FTP - 4 x 2 x 0,22mm² (AWG 24/7) stranded – HFFR-LS- MARINE APPROVED
 <BATCH NR.><Meter MARKING> IEC 60332-3-22/24 or

TKF - InduData - Category 6A S/FTP - 4x2x0,246 mm² (AWG 23/7) stranded – HFFR-LS- MARINE APPROVED
 <BATCH NR.><Meter MARKING> IEC 60332-3-22/24 or

TKF - InduData - Category 6A S/FTP - 4x2x0,246 mm² (AWG 23/1) solid – HFFR-LS- MARINE APPROVED
 <BATCH NR.><Meter MARKING> IEC 60332-3-22/24 or

TKF - InduData - Category 7 S/FTP - 4 x 2 x 0,27mm² (AWG 22/7) stranded - HFFR-LS - MARINE APPROVED
 <BATCH NR.> <Meter MARKING> IEC 60332-3-22/24 or

TKF - InduData - Category 7 S/FTP - 4 x 2 x 0,259mm² (AWG 23/1) solid - HFFR-LS - MARINE APPROVED
 <BATCH NR.> <Meter MARKING> IEC 60332-3-22/24 or

TKF - InduData - Category 7A S/FTP - 4x2x0,264 mm² (AWG 23/1) solid – HFFR-LS- MARINE APPROVED
 <BATCH NR.><Meter MARKING> IEC 60332-3-22/24

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine tests (RT) and selected type tests (ref. to applicable class programs) checked (if not available these tests shall be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years.
 A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE